



# MATERIAL SAFETY DATA SHEET

## LUBRIMATIC ULTRA LUBE (11309 - 11310)

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>TRADE NAME</b>	LUBRIMATIC ULTRA LUBE (11309 - 11310)
<b>Product number</b>	329050, 329060
<b>PRODUCT USE</b>	Lubricating Grease
<b>SUPPLIER</b>	Chemtool Incorporated P.O. Box 538 8200 Ridgefield Road Crystal Lake, IL 60039-0538 USA Tel: (815) 459-1250 Fax: (815) 459-1955
<b>EMERGENCY TELEPHONE</b>	Infotrac U.S. and Canada - (800) 535-5053 Outside the U.S. and Canada - +01-352-323-3500
<b>Date of last issue</b>	2009-01-06

### 2. COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	Mixture	70-90 %
*LITHIUM SOAP AND MIXED BASE THICKENERS	Proprietary	5-15 %
*PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	68649-42-3	<1 %
*BENZENESULFONIC ACID, DODECYL-, CALCIUM SALT	26264-06-2	<0.5 %
*CARBON BLACK	1333-86-4	<0.2 %
*ANTIMONY DIALKYL DITHIOCARBAMATE (NJTSRN 800983-5015P OR CAS# 15890-25-2)	Proprietary	<0.1 %

\* This chemical(s) is hazardous according to OSHA/WHIMIS criteria

#### COMPOSITION COMMENTS

Refer to section eight for exposure limits on ingredients.

Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

\*\* (2) The base oil for this product can be a mixture of any of the following highly refined petroleum streams:

CAS 64741-88-4; CAS 64741-89-5; CAS 64741-96-4; CAS 64741-97-5; CAS 64742-01-4; CAS 64742-52-5; CAS 64742-53-6; CAS 64742-54-7; CAS 64742-55-8; CAS 64742-56-9; CAS 64742-57-0; CAS 64742-62-7; CAS 64742-63-8; CAS 64742-65-0; CAS 72623-83-7; CAS 72623-85-9; CAS 72623-86-0; CAS 72623-87-1.

Carcinogenicity: The petroleum base oils contained in this product have been highly

refined by a variety of processes including solvent extraction, solvent dewaxing and hydrotreating to remove aromatics and improve performance characteristics. None of the oils used are listed as a carcinogen by NTP, IARC, or OSHA.

---

### 3. HAZARDS IDENTIFICATION

---

#### EMERGENCY OVERVIEW

<b>HEALTH HAZARDS, GENERAL</b>	Exposure to vapors generated at high temperatures may cause respiratory irritation.
<b>SENSITIZATION</b>	No known information.
<b>CARCINOGENICITY</b>	See Section 11 for carcinogenicity data of ingredients.
<b>HEALTH WARNINGS</b>	INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. Irritating. INGESTION. Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.
<b>ROUTE OF ENTRY</b>	Inhalation. Skin and/or eye contact. Ingestion.
<b>MEDICAL SYMPTOMS</b>	MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not determined

---

### 4. FIRST AID MEASURES

---

<b>INHALATION</b>	Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product, immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.
<b>EYES</b>	Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.
<b>SKIN</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>INGESTION</b>	DO NOT INDUCE VOMITING! Get medical attention immediately!

---

### 5. FIRE FIGHTING MEASURES

---

<b>FLASH POINT (°C)</b>	224 (435°F) Cd OC (Cleveland open cup).
<b>FLAMMABILITY LIMIT - LOWER(%)</b>	N/D
<b>FLAMMABILITY LIMIT - UPPER(%)</b>	N/D
<b>EXTINGUISHING MEDIA</b>	Use: Carbon dioxide (CO <sub>2</sub> ). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.
<b>SPECIAL FIRE FIGHTING PROCEDURES</b>	Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

---

<b>UNUSUAL FIRE &amp; EXPLOSION HAZARDS</b>	Pressure will increase in over heated, closed containers.
<b>HAZARDOUS COMBUSTION PRODUCTS</b>	Oxides of: Carbon.
<b>PROTECTIVE MEASURES IN CASE OF FIRE</b>	Self-contained breathing equipment and chemical resistant clothing recommended.

## 6. ACCIDENTAL RELEASE MEASURES

<b>PERSONAL PRECAUTIONS</b>	Minimize skin contact.
<b>PRECAUTIONS TO PROTECT THE ENVIRONMENT</b>	Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.
<b>SPILL CLEAN-UP PROCEDURES</b>	Contain spill. Absorb small amounts. Collect and return large amounts to shipping container. Rinse area with water.

## 7. HANDLING AND STORAGE

<b>HANDLING PRECAUTIONS</b>	Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. Avoid spilling, skin and eye contact. Eye wash and emergency shower must be available at the work place.
<b>STORAGE PRECAUTIONS</b>	Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.
<b>STORAGE CRITERIA</b>	Chemical storage.

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	OSHA			5 mg/m3 (oil mist)	
	ACGIH			5 mg/m3 (oil mist)	10 mg/m3 (oil mist)
CARBON BLACK	OSHA			3.5 mg/m3	
	ACGIH			3.5 mg/m3	**A4
	NIOSH	3.5 mg/m3	**Ca		
ANTIMONY DIALKYLDITHIOCARBAMATE (NJTSRN 800983-5015P OR CAS# 15890-25-2)	OSHA			0.5 mg/m3 as Sb	
	ACGIH			0.5 mg/m3 as Sb	

### INGREDIENT COMMENTS

\*\*NIOSH Ca: Potential Occupational Carcinogen.  
 \*\*ACGIH A4: Not Classifiable as a Human Carcinogen.

### PROTECTIVE EQUIPMENT



<b>ENGINEERING CONTROLS</b>	Use engineering controls to reduce air contamination to permissible exposure level.
<b>VENTILATION</b>	No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.
<b>RESPIRATORS</b>	No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.
<b>PROTECTIVE GLOVES</b>	Chemical resistant gloves recommended to prevent prolonged or repeated contact.
<b>EYE PROTECTION</b>	Wear splash-proof eye goggles to prevent any possibility of eye contact.
<b>PROTECTIVE CLOTHING</b>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<b>HYGIENIC WORK PRACTICES</b>	Wash at the end of each work shift and before eating, smoking and using the toilet.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>APPEARANCE/PHYSICAL STATE</b>	Grease.		
<b>COLOR</b>	Black.		
<b>ODOR</b>	Mild (or faint). Petroleum.		
<b>SOLUBILITY DESCRIPTION</b>	Insoluble in water.		
<b>DENSITY</b>	0.89	<b>Temperature (°C)</b>	15.6 (60°F)
<b>VAPOR DENSITY (air=1)</b>	> 5		
<b>VAPOR PRESSURE</b>	< 0.1 mmHg	<b>Temperature (°C)</b>	20 (68°F)
<b>EVAPORATION RATE</b>	< 0.01	<b>Reference</b>	BuAc=1
<b>pH-VALUE, CONC. SOLUTION</b>	N/A		

---

## 10. STABILITY AND REACTIVITY

---

<b>STABILITY</b>	Normally stable.
<b>CONDITIONS TO AVOID</b>	Avoid contact with acids and oxidizing substances.
<b>HAZARDOUS POLYMERIZATION</b>	Will not occur.
<b>POLYMERIZATION DESCRIPTION</b>	Not applicable
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b>	Oxides of: Carbon.

## 11. TOXICOLOGICAL INFORMATION

---

**TOXICOLOGICAL INFORMATION** No experimental toxicological data on the preparation as such is available.

**COMPONENT** LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED\*\*(2)

**TOXICOLOGICAL DATA** Carcinogenicity. IP 346 <3%  
**TOXIC DOSE - LD 50** > 5000 mg/kg (oral rat)  
**TOXIC DOSE - LD 50 SKIN** > 2000 mg/kg (skn rbt)  
**TOXIC CONC. - LC 50** N/A.

**COMPONENT** LITHIUM SOAP AND MIXED BASE THICKENERS

**TOXIC DOSE - LD 50** No Information Available (NIA).  
**TOXIC CONC. - LC 50** No Information Available (NIA).

**COMPONENT** CARBON BLACK

**TOXICOLOGICAL DATA** Carcinogenicity. WHMIS (Canada) D2A - R40  
Acute toxicity. TClO 6 hours. Inhalation. Rat. 7 mg/m3  
**TOXIC DOSE - LD 50** > 15400 mg/kg (oral rat)  
**TOXIC DOSE - LD 50 SKIN** > 3000 mg/kg (skn rbt)  
**CARCINOGENICITY** NTP: Not listed. MAK-3 designation: Substances which cause concern that they could be carcinogenic for man. IARC-2B: The agent is possibly carcinogenic to humans (limited evidence of carcinogenicity in humans).

---

## 12. ECOLOGICAL INFORMATION

---

**ECOLOGICAL INFORMATION** There is no ecological data on the product itself.

---

## 13. DISPOSAL CONSIDERATIONS

---

**DISPOSAL METHODS** Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

---

## 14. TRANSPORT INFORMATION

---

**DOT HAZARD CLASS** Not regulated.  
**REPORTABLE QUANTITY (RQ)** No  
**TDGR CLASS** Not Regulated.  
**SEA TRANSPORT NOTES** Not regulated per IMDG.  
**AIR TRANSPORT NOTES** Not regulated per IATA.

---

## 15. REGULATORY INFORMATION

### US FEDERAL REGULATIONS

COMPONENT	SARA 302	CERCLA	SARA 313
LITHIUM SOAP AND MIXED BASE THICKENERS	No	No	No
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	No	***	N982 - Zn
BENZENESULFONIC ACID, DODECYL-, CALCIUM SALT	No	1 000 lbs	No
CARBON BLACK	No	No	No
ANTIMONY DIALKYLDITHIOCARBAMATE (NJTSRN 800983-5015P OR CAS# 15890-25-2)	No	***	N010 - Sb
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	No	No	No

### REGULATORY STATUS

\*\*\* Indicates that no RQ is assigned to this generic or broad class, although the class is a CERCLA hazardous substance. See 50 Federal Register 13456 (April 4, 1985). Values in Section 313 column represent Category Codes for reporting under Section 313.

### CLEAN AIR ACT

**SARA HAZARD CATEGORIES** None

### US STATE REGULATIONS

COMPONENT	CA	MA	FL	MN	NJ	PA	RI
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)					Yes	Yes	
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS				Yes	Yes	EH	
BENZENESULFONIC ACID, DODECYL-, CALCIUM SALT						EH	
CARBON BLACK	C	Yes			Yes	HS	
ANTIMONY DIALKYLDITHIOCARBAMATE (NJTSRN 800983-5015P OR CAS# 15890-25-2)				Yes		EH	

### STATE REGULATORY STATUS

**CALIFORNIA PROPOSITION 65:** This product may contain the following chemical(s) considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing cancer or reproductive toxicity, and for which warnings are now required:

Carbon black (airborne, unbound particles of respirable size), cancer hazard, CAS# 1333-86-4.

**PENNSYLVANIA RIGHT-TO-KNOW:** This product contains the following chemicals that the state of Pennsylvania has identified as Special Hazardous Substances (SHS), Environmental Hazards (EH), or both (ESHS). The PA regulations require that the MSDS identify all SHS or EH chemicals by chemical name, common name, and CAS Number if they comprise 0.01% or more.

Zinc compounds regulated under CERCLA and SARA 313, Environmental Hazard  
Antimony compounds regulated under CERCLA and SARA 313, Environmental Hazard

Benzenesulfonic acid, dodecyl-, sodium salt, Environmental Hazard, CAS#

25155-30-0

**WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHMIS**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**CONTROLLED PRODUCT CLASSIFICATION**

Not a controlled product.

**GLOBAL INVENTORIES**

COMPONENT	CAN	US	EU	AUS	JAP	KOR	PHLP	CHN
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	NPRI	Yes	EINECS	Yes	Yes	Yes	Yes	Yes
BENZENESULFONIC ACID, DODECYL-, CALCIUM SALT	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes
CARBON BLACK	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes
ANTIMONY DIALKYL DITHIOCARBAMATE (NJTSRN 800983-5015P OR CAS# 15890-25-2)	NPRI	Yes	EINECS	Yes	Yes	Yes	Yes	Yes
LITHIUM SOAP AND MIXED BASE THICKENERS	DSL	Yes	EINECS	No	Yes	Yes	No	No
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes

CANADA CEPA: All components of this product comply with new substance notification requirements under the Canadian Environmental Protection Act (CEPA).

**16. OTHER INFORMATION****NFPA-HMIS HAZARD RATING**

<b>HEALTH</b>	Irritation, minor residual injury (1) - HMIS/NFPA
<b>FLAMMABILITY</b>	Burns only if pre-heated (1) - HMIS/NFPA
<b>REACTIVITY</b>	Normally Stable (0) - HMIS/NFPA
<b>PERSONAL PROTECTION INDEX</b>	B - Safety Eyewear and Gloves
<b>REVISION COMMENTS</b>	Section 2: Ingredients Section 8: Exposure Limits. Section 11: Toxicological Information Section 15: WHMIS
<b>PREPARED BY</b>	Bob Fox
<b>Replacement of MSDS generated</b>	2005-10-28
<b>DATE</b>	2009-01-06
<b>DISCLAIMER</b>	While the information and recommendations set forth herein are believed to be accurate as of the date thereof, the company makes no warranty with respect thereto and disclaims all liability from reliance therein.

\* Information revised since previous MSDS version

**PRINTING DATE:** 2009-01-06